Data	Model	60kW	90kW	120kW
Electrical Specification	Input Voltage	480Vac Three-phase		
	Input Specification	3P+N+PE		
	Input Frequency	50/60Hz (±10%)		
	Output Voltage	200-1000Vdc		
	Output Current	125A	240A	250A
Electrical Parameter	Power Factor	⩾0.99		
	Efficiency	⩾95% (50%-100% load)		
	Stable Voltage Accuracy	⩽±0.5%		
	Stable Current Accuracy	⩽±1%		
Configuration	Inside Power Module	30kW*2	30kW*3	30kW*4
	Network	Ethernet / WIFI / 4G		
	Communication	OCPP 1.6 / OCPP 2.0.1 / TCP		
	Touch-Display	10" Daylight Readable		
	Payment Method	RFID / POS / OCPP		
Security	Multiple Protection	Over/Under Voltage Protection, Overload Protection, Short Circuit Protection, Over/Under Temperature Protection, Surge Protection, Communication Failure.		
	MTBF	100,000 hours		
	Protection Grade	Type 3R		
Working Environment	Operation Temp	-30°C to +50°C (-22°F to +122°F)		
	Working Humidity	5%-95% Without Condensation		
	Working Altitude	<2000m		
	Cooling Method	Fan Cooling		
Product	Cable Length	5m (standard)		
	Warranty	2 years		
	Dimension	850*550*1780mm		
	Net Weight	290kg	310kg	330kg
Optional	Adapters	CCS1 & CHAdeMO		